

PERCOLATOR INSTRUCTIONS

SETTING UP PERCOLATOR: Place percolator on a flat, level surface. Plug in power cord AFTER water and coffee are added. After placing in a secure location, remove the cover and inner basket. Make sure the spigot is closed before filling with water. Fill percolator with cold, fresh water according to the markings on the inside for the number of cups desired (use cold water - the automatic brewing cycle is timed to begin with a cold water start). Wet the coffee basket to help keep small particles of coffee from sifting through. Add the desired amount of coffee to the basket. Replace the percolator cover and secure into position by tuning cover clockwise until the cover tabs fit into handle slots.

BREWING: Once the water and coffee are added, plug the power cord into the necessary outlet. Brewing will automatically begin and stop after brewing process is complete. Completion of brewing is indicated by the red indicator light. The percolator will automatically switches to "keep warm" setting to preserve fresh tasting coffee at hot, ready to serve temperature. For best flavor, remove coffee basket and pump tube when brewing is complete. To dispense, use spigot carefully as the liquid and percolator will be hot.

PERCOLATOR AND PARTS WILL BE HOT WHEN POWER IS ON.

USE ONLY ON FLAT, LEVEL SURFACES.

REMOVE PERCOLATOR PARTS CAREFULLY AS THEY ARE MOST LIKELY TO BE HOT.

PLUG IN COFFEE URN AFTER THE WATER AND COFFEE ARE ADDED.